


1		2		3		4		5		6	
Document No.	QR4-700-T-003	REV.	A/0	REV.	DESCRIPTION	REVISOR	DATE	APPROVED			
		0				JUNMA	04.05.2017	David			



SPECIFICATIONS	
Part's Number	2CCM35-1
Frequency(GHz)	297~400
Direction	CW
Insertion Loss(dB) TYP/MAX	0.5/0.5
Insertion Loss Ripple	
Isolation(dB) TYP/MIN	18/17
Return Loss(dB) TYP/MIN	17.69/16.54
3rd IMD(dBc) TYP/MAX	
Power FWD/REV/PK(Watt)	300/300/300
Operating Temperature(°C)	25/-10~+50
Storage Temperature(°C)	
2nd/3rd Harmonic(dBc)	
Termination/Attenuator(Watt/dB)	300
Tab(W×LG×THK)(mm[Inch])	
Additional Notes	GWB

**DORADO INTERNATIONAL** **DORADO Millimeter Wave**

<b>MATERIAL:</b>	<b>DWG NO:</b> 2CCM35-1			
<b>SURFACE TREATMENT:</b>	DWG BY:	JUNMA	04.05.2017	SCALE
	CHK'D BY:			1:2
<b>DESCRIPTION:</b> BROADBAND CIRCULATOR	APPV'D BY:			A4
	Unit: mm[inch]	Tolerance: Liner: ±0.25 Anguar: ±0.5°	The First:	



This document is the property of DORADO Millimeter Wave. It cannot be copied, duplicated, used for manufacturing purposes or communicated to third party as a whole or partly, without the written consent of DORADO Millimeter Wave.