


1		2		3		4		5		6	
Document No.	QR4-700-T-003	REV.	A/0	REV.	DESCRIPTION	REVISOR	DATE	APPROVED			
		0				LH.Mao	01.13.2017	David			

SPECIFICATIONS	
Part's Number	4IMG26-1
Frequency(GHz)	25.27-27.0
Direction	CW
Insertion Loss(dB)MAX	1.3
Insertion Loss Ripple	
Isolation(dB)MIN	19
Return Loss(dB)MIN	17.21
3rd IMD(dBc)MAX	
Power FWD/REV/PK(Watt)	1/1/-
Operating Temperature(°C)	-30~+70
Storage Temperature(°C)	
2nd/3rd Harmonic(dBc)	
Termination/Attenuator(Watt/dB)	1
Tab(W×LG×THK)(mm[Inch])	
Additional Notes	GWB



DORADO DORADO Millimeter Corp
INTERNATIONAL

MATERIAL: _____ **DWG NO:** 4IMG26-1

SURFACE TREATMENT: _____

DWG BY:	LH.Mao	01.13.2017	SCALE
CHK'D BY:			
APP'V'D BY:			6:1
Unit:	Tolerance:	The First:	A4
mm[inch]	Liner: ±0.25 Anguar: ±0.5°		

DESCRIPTION:
MICROSTRIP ISOLATOR



This document is the property of DORADO Millimeter Corp. It cannot be copied, duplicated, used for manufacturing purposes or communicated to third party as a whole or partly, without the written consent of DORADO Millimeter Corp.