


1		2		3		4		5		6	
Document No.	QR4-700-T-003					REV.	DESCRIPTION	REVISOR	DATE	APPROVED	
REV.	A/0					0		LH.Mao	01.13.2017	David	

SPECIFICATIONS	
Part's Number	4CMG22-1
Frequency(GHz)	21.2 – 23.6
Direction	CW
Insertion Loss(dB)MAX	1.1
Insertion Loss Ripple	
Isolation(dB)MIN	18
Return Loss(dB)MIN	17.69
3rd IMD(dBc)MAX	
Power FWD/REV/PK(Watt)	1/1/-
Operating Temperature(°C)	-30~+70
Storage Temperature(°C)	
2nd/3rd Harmonic(dBc)	
Termination/Attenuator(Watt/dB)	1
Tab(W×LG×THK)(mm[Inch])	
Additional Notes	GWB



DORADO Millimeter Corp				
MATERIAL:		DWG NO: 4CMG22-1		
SURFACE TREATMENT:		DWG BY:	LH.Mao	01.13.2017
		CHK'D BY:		SCALE
DESCRIPTION: MICROSTRIP CIRCULATOR		APP'V'D BY:		6:1
		Unit: mm[inch]	Tolerance: Liner: ±0.25 Anguar: ±0.5°	The First:
				A4



This document is the property of DORADO Millimeter Corp. It cannot be copied, duplicated, used for manufacturing purposes or communicated to third party as a whole or partly, without the written consent of DORADO Millimeter Corp.