


1		2		3		4		5		6	
Document No.	QR4-700-T-003	REV.	A/0	REV.	DESCRIPTION	REVISOR	DATE	APPROVED			
		0				LH.Mao	03.22.2017	David			



SPECIFICATIONS	
Part's Number	4ICC10-2
Frequency(GHz)	8.00~12.00
Direction	CW
Insertion Loss(dB) TYP/MAX	0.5/0.7
Insertion Loss Ripple	
Isolation(dB) TYP/MIN	18/15
Return Loss(dB) TYP/MIN	17.69/13.98
3rd IMD(dBc)MAX	
Power FWD/REV/PK(Watt)	1/-/-
Operating Temperature(°C)	-196/+15 ~ +35
Storage Temperature(°C)	
2nd/3rd Harmonic(dBc)	
Termination/Attenuator(Watt/dB)	
Tab(W×LG×THK)(mm[Inch])	
Additional Notes	GWB

DORADO Millimeter Wave				
MATERIAL:		DWG NO:		
		4ICC10-2		
SURFACE TREATMENT:		DWG BY:	LH.Mao	03.22.2017
		CHK'D BY:		SCALE
DESCRIPTION:		APPV'D BY:		1:1
Cryogenic Isolator		Unit:	Tolerance:	The First:
		mm[inch]	Liner: ±0.25	
			Anguar: ±0.5°	A4



This document is the property of DORADO Millimeter Wave. It cannot be copied, duplicated, used for manufacturing purposes or communicated to third party as a whole or partly, without the written consent of DORADO Millimeter Wave.